



The Samsung 40" 400UX-3 LCD video wall display features advanced cooling technologies that allow reliable operation 24 hours a day, 7 days a week.

With thin 12.5mm bezels, you can build virtually seamless video walls.

With full HD 1920 x 1080 resolution, 700cd/m<sup>2</sup> brightness, and a dynamic contrast ratio of 10,000:1, the display presents beautiful images in eye-catching high-definition.

### Features:

- 1920 x 1080 (16:9) Resolution | 3000:1 Contrast Ratio
- Embedded video matrix processor supports 1x1 to 10x10 wall formats
- Picture-in-Picture Configuration | Built-In Speakers | Narrow Bezel
- DVI-Out Interface | HDMI x 2
- 38.5 lbs | 36.0 x 20.7 x 4.6 inches (W x H x D)

### Detailed Specifications

<b>Native Resolution</b>	1920 x 1080	<b>Colors Supported</b>	8-Bit-16.7 Million
<b>Active Display Area</b>	34.9 x 19.6" (885.6 x 498.2mm)	<b>Color Gamut</b>	72%
<b>Aspect Ratio</b>	16:9	<b>Internal Interface</b>	Analog/Digital
<b>Display Format</b>	1080p	<b>Scanning Frequency</b>	H: 30kHz-81kHz V: 56Hz-85Hz 148.5MHz Maximum Pixel Frequency
<b>Contrast Ratio</b>	3000:1	<b>Sync Type</b>	Separate H/V Sync, Composite, Sync on Green
<b>Dynamic Contrast Ratio</b>	10000:1	<b>Features</b>	Lamp Error Detection, Anti Retention, Temperature Sensor, RS232C/RJ45 MDC, Built in Speaker (10W + 10W), Plug and Play (DDC2B), PIP/PBP, Video Wall (10x10), Pivot Display, Button Lock, Digital Daisy Chain, Smart Scheduling, Smart F/W update
<b>Pixel Pitch</b>	0.46125 mm (H) x 0.46125 mm (V)	<b>Speakers</b>	2 Built in 10W
<b>Response Time</b>	8ms	<b>Compliance</b>	ENERGY STAR 5.0
<b>Brightness</b>	700cd/m <sup>2</sup>	<b>Dimensions</b>	36.0 x 20.7 x 4.6 inches (W x H x D)
<b>Viewing Angle</b>	178° Horizontal, 178° Vertical	<b>Weight</b>	38.5 lbs
<b>Tilt/Swivel Range</b>	None		
<b>Touch Screen</b>	No		
<b>Inputs/Outputs</b>	RGB Analog D-Sub x 1 DVI-D x 1 Display Port Inputs x 2 Video CVBS x 1, HDMI x 1, HDMI x 2, Component (D-sub 15-pin) Input x 1 RCA (L/R) x 1, Stereo Mini Jack x 1 DVI-D (Loop Out) RGB Output x 1 Stereo Mini Jack x 1 5V (for SBB) Power Output x 1 RS-232C (In/Out) x 1, RJ-45 x 1 External Sensors: Stereo Mini Jack (IR In/Out) x 1 Mini USB (Ext. BR/IR Sensor) x 1		



**Displays Can be Rented Individually**